## **PRODUCT INFORMATION SHEET**



## **Epifanes Paint Remover**

Description	Paint Remover of various coatings
Туре	Water based
Properties	A safe and odorless remover of almost all one-and two-part coatings, var- nishes, antifoulings and epoxy based paints. Effectively working and non- evaporating. Suitable for use on vertical and overhanging areas. pH neu- tral, biologically degradable, does not contain any lyes, acids or biocides and is harmless to the substrate. May be applied in full sunshine and be- low freezing.
Field of application	Removal of layers on fiberglass, steel, wood and aluminum. Do not apply on soft plastics. Always first make a small test patch to check compatabili- ty. After use, remove all remaining material prior to applying any paint layer.
Colour	green
Density	1,17kg/dm³
Viscosity	Not determined
Solids contents	100%
VOC - level	73 grams/litre
Packing	1000ml.
Colverage	1000ml. is sufficient for approx. 20-40 sq. ft./2-4 m <sup>2</sup> .
Shelf life	In closed container stored in a dark location between 5 - 25°C., approx. 2 years
Tips for application	Stir well prior to use. Apply one thick layer by medium long natural haired brush. Avoid overbrushing. Depended on the paint layer to be removed allow the paint remover 30 minutes to 24 hours to react. Scrape clean with filling knife or shave hook. Remove remaining paint remover by washing the surface with a water.
Reaction time	Unlike old style paint removers based on methylene chloride, this paint remover will need more time to react. Reaction time depends on type and thickness of coating.
Safety	The user of this product should obey all national laws and legislation con- cerning health, safety and environmental hazard. For more information on health and safety, refer to the Material Safety Data Sheet of this product.

Allthough the facts and suggestions in this product information sheet are based on our own research and field experiences and are believed reliable, we cannot simply be held responsible for performance or results obtained through the use of this product. Ineffectiveness or other unintended consequences may result, because of such factors as weather, conditions, presence or other materials or the manner of preparation, use or application all of which are beyond W. Heeren & Zoon's control. All such risks are assumed by user.

DISCLAIMER OF WARRANTIES. Seller makes no express warranties. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. In the event a warranty is created by law, buyer's EXCLUSIVE REMEDY shall be the replacement of any defective product. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss ) shall be available to buyer.